Platinum Temperature Sensor **FMA- 2146**

Technical Data

Resistance at 0°C	1000 Ω
Temperature coefficient (0°C up to +100°C)	3.85 · 10^{-3} K^{-1}
Tolerance classes according to DIN EN 60751	• F 0,1 (0°C - +150°C) • F 0,15 (-30°C - +300°C) • F 0,3 (-50°C - +500°C) • F 0.6 (-50°C - +600°C)
Operating temperature range depending on lead material:	
AgPd5, Au-coated Ni-wire	-50 °C up to +400 °C
Pt-coated Ni-wire	-50 °C up to +500 °C (short-time up to +550 °C)
Pt	-50 °C up to +600 °C
Measurement current (DC) at 25 °C	0.1 mA
Maximal permissible peak current (DC) at 25 °C	0.3 mA
Insulation resistance	> 10 MΩ
Self-heating at 0 °C	< 0.5 K / mW
Thermal response time	
Flowing water (v = 0.2 m/s)	$T_{0.5}$ = 0.07s, $T_{0.9}$ = 0.3s
Flowing air (v = 1 m/s)	$T_{0.5}$ = 6 s, $T_{0.9}$ = 20 s

Resistance value R_t [Ω] at temperature t

	Tolerance class			
t	F 0,1 [Ω]	F 0,15 [Ω]	F 0,3 [Ω]	F 0,6 [Ω]
0 °C	1000±0.4	1000±0.6	1000±1.2	1000±2.4
+100 °C	1385.1±1	1385.1±1.3	1385.1±3	1385.1±6

R_t measuring point	2 mm from wire end
Maximal Resistance Change at UCT 250 h	< 0.1 %
Specification	DIN EN 60751
Type	Film sensor

Technology: Advanced thin-film-technology (ceramic carrier with a structured platinum layer, covered with a passivation layer)

Operating conditions: Unprotected application only in dry environments without any contamination

Conformity: 2011/65/EU Restriction of the use of Hazardous Substances Directive (RoHS)

Dimensions [mm]



Please note
Leads are not angled ex works.

	FMA- 2146 2x5x1.3	FMA- 2146 2x5x1.0	Leads	AgPd5	NiAu	NiPt	Pt
H1 [mm]	1.3 ± 0.2	1± 0.2	l [mm]	15 ± 1	15 ± 1	10 ± 1	7 ± 1
H2 [mm]	0.65	0.4	d [mm]	0,25	0,2	0,2	0,2

Functional performance

according to DIN EN 60751



Picture 1: Resistance and temperature tolerances of Pt1000 (Please note - the operating temperature range depends on lead material!)

Temperature range from -50 °C up to 0 °C:

$R_t = R_o \cdot (1 + A \cdot t + B \cdot t^2 + C \cdot (t - 100\ °C) \cdot t^3)$

Temperature range from 0°C up to +600°C:

$R_t = R_o \cdot (1 + A \cdot t + B \cdot t^2)$

Tolerance classes according to DIN EN 60751:

Class F 0,1 (0°C - +150°C): $\Delta t = \pm (0.1 + 0.0017 \cdot |t|)$

Class F 0,15 (-30°C - +300°C): $\Delta t = \pm (0.15 + 0.002 \cdot |t|)$

Class F 0,3 (-50°C - +500°C): $\Delta t = \pm (0.3 + 0.005 \cdot |t|)$

Class F 0,6 (-50°C - +600°C): $\Delta t = \pm (0.6 + 0.01 \cdot |t|)$

Whereby:

R_t … Resistance [Ω] at temperature t

R_o … Resistance [Ω] at 0 °C

t … Temperature [°C]

Δt …Permissible temperature deviation at t [°C]

A = 3.9083 · 10^{-3} $°C^{-1}$

B = - 5.775 · 10^{-7} $°C^{-2}$

C = - 4.183 · 10^{-12} $°C^{-4}$

Fields of application

- Industrial electronics
- Building automation
- Automotive electronics
- Energy and environmental engineering
- Safety and medical engineering

Ordering examples

Construction	Class of accuracy	Leads (ø d x l [mm] lead material)	Operating temperature range [°C]
FMA- 2146 2x5x1.3	**F 0,15**	**0.25x15 AgPd5**	**-50/+400**
FMA- 2146 2x5x1.0	**F 0,3**	**0.2x10 NiAu**	**-50/+400**
FMA- 2146 2x5x1.0	**F 0,6**	**0.25x15 AgPd5**	**-50/+400**

Other classes of accuracy and wire lengths are available on request.

© UST Umweltsensortechnik GmbH, 2016-2022
Errors excepted. Subject to alterations for this information and technological changes.

Made in Germany

UST Umweltsensortechnik GmbH, Dieselstr. 2 und 4,
99331 Geratal OT Geschwenda, Germany
Tel. +49 36205 713-0
Fax +49 36205 713-10
info@umweltsensortechnik.de
www.umweltsensortechnik.de